

	2 - LANE SLIDE W=1600	Width	1600	[mm]
		Pump Efficiency	90	[m³/h]
		Optimal Length	20-40	[m]
		Average Slope	13-20	[%]
	WIDE 2 - LANE SLIDE W=3400	Width	3400	[mm]
		Pump Efficiency	90	[m³/h]
		Optimal Length	20-40	[m]
		Average Slope	13-20	[%]
	3 - LANE SLIDE W=2500	Width	2500	[mm]
		Pump Efficiency	120	[m³/h]
		Optimal Length	20-40	[m]
		Average Slope	13-20	[%]
	4 - LANE SLIDE W=3400	Width	3400	[mm]
		Pump Efficiency	160	[m³/h]
		Optimal Length	20-40	[m]
		Average Slope	13-20	[%]
	MULTILANE SLIDE	Width	>3400	[mm]
		Pump Efficiency	≥160	[m³/h]
		Optimal Length	20-40	[m]
		Average Slope	13-20	[%]



As the name suggests, this construction is composed of many tracks parallel and connected to each other, which allows several people to slide simultaneously with no risk of collision. Additional attraction related to the slide is a possibility of friendly competition between the users. The slide is available in options 2,3,4 and 5-track, and more than that, it allows to use tracks from 2 to 5 at the same time.

